

Luke

Mini IP-PBX



- 50 SIP extensions
- 12 Concurrent Calls
- Auto-attendant
- 2 FXO trunks
- 2 FXS extensions
- 3 SIP trunks



Supported standards:

SIP RFC 3261 Compliance
Voice Coders: G.711 a/ μ , G.729A and G.723.1,
G.726-32K, GSM
T.38, T.30 FAX support
Video Codec Pass-Thru: H.263, H.264
MIME, SMIME authentication
RTP, sRTP
Internet: DHCP, Static IP, PPPoE, PPTP
Network: NAT & DHCP server

Call Features

Call Hold, Call Waiting, Call Parking, Call Pickup
Blind Call Transfer, Attended Call Transfer
Call Forward on Busy, No Answer or Always
Do Not Disturb
Speed Dial
Outgoing & Incoming call blocking
Hot Line, Warm Line
Ring Groups & Hunt Groups
Direct Inward Dialing (DID)
Call Queuing
3-way calling
Call Logging, Call Reporting
Busy Lamp Field (BLF) per RFC4235

Voice Mail

Personal greeting
Multi-Languages support
MWI notification (option)
Email notification
Redirect to PBX /SIP/ PSTN

Auto Attendant

Web-Based Auto Attendant Flow Editor
Scheduled Special Announcement
Holidays Working Time Support
Multiple Language Support

Call Conference

Conference Calling
Meeting Rooms
Up-to 6 Participants per Room

Management

Web-Based management
User and administration configuration mode
NTP synchronization
System event Syslog
Scheduled Backup
Firewall and DMZ
Access control
USB device Restore and Backup configuration
VXML Based IVR

Physical

Two WAN ports, for connecting to Internet
One LAN port for connecting to Private Network
One USB port
4 RJ-11 ports, 2 for FXS and 2 for FXO
IEEE802.11n, 2T2R
Dimension: W 22.2x H 3.3x D 14.5 cm (excl. Stand)
Weight: 450g (without packing)
One unit packing dimension: 55 x 37.5 17.5 CM

Environmental

0°C~45°C,
10%~90% relative humidity, non-condensing